

SKTECH-60 Series of Industrial Endoscope



More efficient detection

SK Tech series is equipped with a number of detection functions, with advanced technology, and comprehensive functions, which assists the inspectors to complete the inspection work efficiently.



Optical fiber illumination for clearer images



More probes for optional



Quick to change probes



5 inch screen, more convenient to watch



WIFI wireless transmission (for optional)



Temperature warning (for optional)

Host	Dimension	350*155*59mm
	Display	5 inch industrial LCD screen
	Outputport	HDMI video output, MicroUSB、TF card slot
	Storage	32G
	Power	Special rechargeable lithium battery pack, online charging, battery life \geq 4 hours
	IP grade	IP54
	Working temperature	-10°C ~ 50°C
	Storage temperature	-20°C ~ 60°C
	Relative humidity	Max 95%, No condensation
System	Operation System	Multifunctional operating system
	Operation method	Button navigation, dual camera and video buttons
	Support Function	With freeze, zoom, photo, flip, video playback, analog ruler functions
	File Format	Image: JPEG (JPG), Video: AVI
	Support Language	Chinese (Simplified and Traditional), French, English, German, Spanish, Italian, Japanese
Packing Case	Weight	3.9kg
	L*W*H	47.9*38.7*15.5cm

Camera and Probe










There are several length and diameter for V series for you to choose according to your requirement.

Model		V60					
		V6010	V6020	V6030	V6040	V6050	V6060
Lens	Direction	Direct view/Side view/Double view					
	View angle(θ)	120°					
	DOF	3mm~30mm, 8mm~150mm, 10mm~200mm, 50mm~infinity					
	Pixel	1MP					
	Illuminating system	Rear high-power LED fiber optic transmission					
Probe	Length(L)	13±0.5mm					
	Diameter(D)	6mm					
	Articulating	360° full direction articulation					
	Bending Angle(α)	170°±10°	160°±10°	150°±10°	130°±10°	120°±10°	
	IP grade	IP67					
	Working temperature	-20°C~70°C					
Insert tube	Length	1m	2m	3m	4m	5m	6m
	Material	Flexible (tungsten braided tube)					



	V (Direct View)	VC (Side view)	VS (Double view)
Lens direction			
View angle(θ)			
DOF			
Probe Length(L)			
Probe diameter(D)			
360°articulation			
Bending angle(α)			

Packing list

No	Name	PCS	Unit	Photos
1	Host	1	pcs	
2	Battery	1	pcs	
3	Memory Card	1	pcs	
4	Card reader	1	pcs	
5	Tripod	1	pcs	
6	USB cable	1	pcs	
7	Charger	1	pcs	
8	User manual	1	pcs	<div style="text-align: center;"> <p>Industrial Endoscope</p>  </div>
9	Guarantee Card	1	pcs	

Manufactured and Distributed by
SK TECHNOLOGIES INDIA PRIVATE LIMITED
 1410, Kamdhenu Commerz,
 Plot No 2, Sector 14, Kharghar, Navi Mumbai 410210

